

Please amend the claims as follows:

1. (Cancelled)
2. (Currently Amended) A socket wrench extension ~~for engagement with a socket~~ and a socket wrench comprising:
  - a. a main body having
    - a first end defining a cavity having a square cross-section and adapted to receive a portion of the socket wrench,
    - an opposite second end, and
    - an axis that extends through said first and said second ends;
  - b. a drive column proximate said main body second end, wherein said drive column is adapted to be received in a square cavity formed in one end of the socket and defining a longitudinal axis that is coincident with said main body axis;
  - c. a concave recess formed in said drive column; and
  - d. a shoulder formed intermediate said main body second end and said drive column annular recess, said shoulder having a cross section that is larger than a cross section of said drive column recess and smaller than a cross section of said main body, wherein each of said cross sections are taken perpendicular to said main body axis, and
  - e. a socket including a first end having a square hole defined by a plurality of sidewalls, each said sidewall defining a concave portion therein,wherein said drive column is receivable in the square cavity formed in the socket in
  - a first position in which said drive column axis intersects an axis of the socket at a non-zero angle such that an end portion of said drive column distal from said main body is received in one of said concave portions, and
  - a second position in which said drive column axis is coincident with the axis of the socket and said shoulder is matingly received in the square cavity of the socket.
3. (Original) The socket wrench extension for engagement with a socket and a socket wrench of claim 2, further comprising:

- a. a blind bore defined in said drive column, said blind bore having an axis that is perpendicular to said drive column axis;
  - b. a detent that is received in said blind bore, and
  - c. a spring that is received intermediate said blind bore and said detent.
4. (Previously Presented) The socket wrench extension for engagement with a socket and a socket wrench of claim 3, wherein said detent is a ball biased radially outward from said blind bore.
5. (Amended) A socket wrench extension and a socket comprising:
- a. a socket defining a cavity having a square cross-section therein and a second end adapted to engage a fastener, said square ~~hole~~ cavity being defined by a plurality of sidewalls, each said sidewall defining a concave groove portion therein; and
  - b. a socket wrench extension having
    - i. a main body that has
      - a first end defining a cavity having a square cross-section and adapted to receive a portion of a socket wrench,
      - an opposite second end, and
      - a longitudinal axis that extends through said first and said second ends;
    - ii. a drive column proximate said main body second end, wherein said drive column is adapted to be received in said socket first end square cavity, said drive column having a longitudinal axis that is coincident with said main body axis;
    - iii. a concave recess formed in said drive column; and
    - iv. a shoulder formed intermediate said main body second end and said drive column annular recess, said shoulder having a cross section that is larger than a cross section of said drive column recess and smaller than a cross section of said main body, wherein each of said cross sections are taken perpendicular to said main body axis, and
- wherein said drive column is receivable in said socket first end cavity in

a first position in which said drive column axis intersects an axis of said socket at a non-zero angle such that a portion of said drive column distal from said main body is received in one of said concave groove portions formed in said sidewalls, and

a second position in which said drive column axis is coincident with said socket axis and said shoulder is matingly received in said socket first end square cavity so that said socket first end abuts said main body second end.

6. (Amended) A socket wrench extension and a socket comprising:

- a. a socket having a first end and a plurality of walls defining a cavity having a square cross-section therein, said cavity walls defining a concave portion therein, and a second end adapted to engage a fastener; and
- b. a socket wrench extension having
  - i. a main body that has
    - a first end defining a cavity having a square cross-section and adapted to receive a portion of a socket wrench,
    - an opposite second end, and
    - a longitudinal axis that extends through said first and said second ends;
  - ii. a drive column proximate said main body second end, wherein said drive column is adapted to be received in said socket first end square cavity, said drive column having a longitudinal axis that is coincident with said main body axis;
  - iii. a detent received in said drive column;
  - iv. a concave recess formed in said drive column; and
  - v. a shoulder formed intermediate said main body second end and said drive column annular recess, said shoulder having a cross section that is larger than a cross section of said drive column recess and smaller than a cross section of said main body, wherein each of said cross sections are taken perpendicular to said main body axis, and

wherein said main body is longer than said drive column, and

wherein said drive column is receivable in said socket first end square cavity in  
a first position in which said drive column axis intersects an axis of said  
socket at a non-zero angle such that said detent is received in a first of said  
concave portions and a portion of said drive column opposite of said detent is  
received in a second of said concave portions opposite of said first concave  
portion, and

a second position in which said drive column axis is coincident with said  
socket axis and said shoulder is matingly received in said socket first end square  
cavity so that said socket first end abuts said main body second end.

7. (Currently Amended) A socket wrench extension ~~for engagement with a socket~~ and a  
socket wrench comprising:

- a. a socket defining a cavity having a square cross-section therein and a second  
end adapted to engage a fastener, said square hole being defined by a plurality  
of sidewalls, each said sidewall defining a concave portion therein;
- b. a main body having
  - a first end defining a cavity having a square cross-section and adapted to  
receive a portion of the socket wrench,
  - an opposite second end, and
  - an axis that extends through said first and said second ends;
- c. a drive column proximate said main body second end, wherein said drive  
column is adapted to be received in a square cavity formed in one end of the  
socket and defining a longitudinal axis that is coincident with said main body  
axis; and
- d. a concave recess formed in said drive column that bisects said drive column  
into a first part distal from said main body second end and a second part  
proximate said main body second end; and

wherein said drive column is receivable in the square cavity formed in the socket in  
a first position in which said drive column first part is within said drive socket  
square cavity and said drive column second part is not so that said axis of said drive column

intersects an axis of the socket at a non-zero angle such that a portion of said drive column distal first part is received in one of said concave portions formed in said sidewalls, and

a second position in which both said first and said second drive column parts are received in said socket square cavity and said drive column axis is coincident with the axis of the socket.